




Specifications

MODELS		AWP™-36S	
MEASUREMENTS	US	Metric	
Working height*	42 ft 5 in	13.10 m	
Platform height	36 ft 5 in	11.10 m	
A Height - stowed (Standard)	9 ft 1.5 in	2.78 m	
stowed (RT)			
B tilted back** (Standard)	6 ft 3.5 in	1.92 m	
C Length - stowed (Standard)	4 ft 7 in	1.40 m	
stowed (RT)			
D Length - tilted back**	9 ft 9 in	2.97 m	
E Width (Standard)	2 ft 5 in	.74 m	
Width (RT)			
PRODUCTIVITY			
Lift capacity	350 lbs	159 kg	
ANSI/CSA:			
F Outrigger footprint (l/w) (Standard)	6 ft 11 in/6 ft 3 in	2.1/1.9 m	
Outrigger footprint (l/w) (RT)			
H Corner access*** (Standard)	2 ft 5 in	.74 m	
Corner access*** (RT)			
I Wall access front/side (Standard)	1 ft 2 in/2 ft 1 in	.36/.64 m	
Wall access front/side (RT)			
CE/AUS/PB Indoor:			
F Outrigger footprint (l/w) (Standard)	6 ft 11 in/6 ft 3 in	2.12/1.91 m	
Outrigger footprint (l/w) (RT)			
H Corner access*** (Standard)	2 ft 5 in	.74 m	
Corner access*** (RT)			
I Wall access front/side (Standard)	1 ft 2 in/2 ft 1 in	.36/.64 m	
Wall access front/side (RT)			
CE/AUS/PB Outdoor:			
F Outrigger footprint (l/w) (Standard)	11 ft 7 in/10 ft 11 in	3.53/3.33 m	
Outrigger footprint (l/w) (RT)			
H Corner access*** (Standard)	3 ft 4 in	1.02 m	
Corner access*** (RT)			
I Wall access front/side (Standard)	3 ft 4 in/4 ft 4 in	1.02/1.32 m	
Wall access front/side (RT)			
Platform Dimensions: (l/w/h)			
Standard	27/26/44.75 in	.69/.66/1.14 m	
Gated standard	27/26/44.75 in	.69/.66/1.14 m	
Gated narrow	26/20/44.75 in	.66/.51/1.14 m	
Standard fiberglass	29/26.5/43.5 in	.74/.67/1.10 m	
POWER			
Power source - AC or DC models	12V DC / 110/50-60 Hz or 220/50-60 Hz AC		
WEIGHT			
AC models (Standard)	1,017 lbs	461 kg	
AC models (RT)			
DC models (Standard)	1,107 lbs	502 kg	
DC models (RT)			
Air motor (Standard)			
Air motor (RT)			
STANDARDS COMPLIANCE			
	ANSI A92.3, CSA B354.1, EN 280, AS 1418.10		



* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Tilt back height with standard platform. For tilt back height with other platforms, please contact your sales representative.
 *** Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.