



MODEL E600J/M600J

REACH SPECIFICATIONS

Platform Height	60 ft 3 in. (18.36 m)
Horizontal Outreach	43 ft 3 in. (13.18 m)
Swing	400 Degrees Non-Continuous
Platform Capacity	500 lb (227 kg)
Platform Rotator	180 Degrees Hydraulic
Jib (range of articulation)	144 Degrees (+74, -70) Vertical
JibPLUS®	N/A

DIMENSIONAL DATA

A. Platform Size	30 x 72 in. (0.76 x 1.83 m)
B. Overall Width	7 ft 11 in. (2.41 m)
C. Tailswing	4 ft (1.22 m)
D. Stowed Height	8 ft 4 in. (2.54 m)
E. Stowed Length	30 ft 9 in. (9.37 m)
F. Wheelbase	9 ft (2.74 m)
G. Ground Clearance (Axle)	12 in. (30 cm)
(Chassis)	23 in. (58 cm)
Gross Vehicle Weight*	14,900 lb (6,759 kg)
Max. Ground Bearing Pressure**	.52 psi (3.7 kg/cm ²)

CHASSIS

Drive Speed	3.0 mph (4.8 kmph)
Gradeability 2WD/4WD	30%/45%
Turning Radius, (Inside)	4 ft (1.22 m)
Turning Radius, (Outside)	15 ft 4 in. (4.67 m)
Axle Oscillation	8 in. (20 cm)
Tire Size/Type	36 x 14-22.5 Non-Marking Pneumatic

POWER SOURCE

Electrical System	48V DC
Batteries	8 x 6V, 415 amp-hr
Drive Motors	Dual Electric Traction
Brakes	Spring Applied Multiple Discs
Hydraulic Motor/Pump	Series Wound Motor/Gear Pump
Hydraulic Reservoir	15 gal. (56.78 L)
Generator Set (M Models)	Fully Automatic, 45 amp
	Kubota 6.7 hp Diesel Engine
Engine Fuel Tank (M Models)	13 gal. (49.21 L)
Generator Noise Level (at max. rpm)	70 dBA @ 7 meters

*Certain options or country standards will increase weight.
**Ground bearing pressure applies to standard tires.

MODEL E600JP/M600JP

REACH SPECIFICATIONS

Platform Height	60 ft 4 in. (18.39 m)
Horizontal Outreach	44 ft 5 in. (13.54 m)
Swing	400 Degrees Non-Continuous
Platform Capacity	500 lb (227 kg)
Platform Rotator	180 Degrees Hydraulic
Jib (range of articulation)	145 Degrees (+89, -56) Vertical
JibPLUS®	180 Degrees Horizontal

DIMENSIONAL DATA

A. Platform Size	30 x 72 in. (0.76 x 1.83 m)
B. Overall Width	7 ft 11 in. (2.41 m)
C. Tailswing	4 ft (1.22 m)
D. Stowed Height	8 ft 4 in. (2.54 m)
E. Stowed Length	33 ft 4 in. (10.16 m)
F. Wheelbase	9 ft (2.74 m)
G. Ground Clearance (Axle)	12 in. (30 cm)
(Chassis)	23 in. (58 cm)
Gross Vehicle Weight*	15,200 lb (6,895 kg)
Max. Ground Bearing Pressure**	.51 psi (3.6 kg/cm ²)

CHASSIS

Drive Speed	3.0 mph (4.8 kmph)
Gradeability 2WD/4WD	30%/45%
Turning Radius, (Inside)	4 ft (1.22 m)
Turning Radius, (Outside)	15 ft 4 in. (4.67 m)
Axle Oscillation	8 in. (20 cm)
Tire Size/Type	36 x 14-22.5 Non-Marking Pneumatic

POWER SOURCE

Electrical System	48V DC
Batteries	8 x 6V, 415 amp-hr
Drive Motors	Dual Electric Traction
Brakes	Spring Applied Multiple Discs
Hydraulic Motor/Pump	Series Wound Motor/Gear Pump
Hydraulic Reservoir	15 gal. (56.78 L)
Generator Set (M Models)	Fully Automatic, 45 amp
	Kubota 6.7 hp Diesel Engine
Engine Fuel Tank (M Models)	13 gal. (49.21 L)
Generator Noise Level (at max. rpm)	70 dBA @ 7 meters

*Certain options or country standards will increase weight.
**Ground bearing pressure applies to standard tires.

PERFORMANCE FEATURES

Standard Features:

- 6 ft (1.83 m) Articulating Jib
- 6 ft (1.83 m) Vertical and Lateral Articulating Jib (E600JP and M600JP Only)
- Operators Tool Tray
- 30 x 72 in. (0.76 x 1.83 m) Side Entry Platform
- Inward Self-Closing Swing Gate
- 180 Degree Hydraulic Platform Rotator
- Platform Console Machine Status Light Panel*
- 110V-AC GFI Receptacle in the Platform
- 5 Degree Tilt Alarm/Indicator Light
- Hourmeter
- Battery Condition Indicator
- Lifting/Tie Down Lugs
- 14 x 22.5 Non-Marking Pneumatic Tires
- 400 Degree Non-Continuous Rotation
- Removable Battery Box
- Oscillating Axle
- Manual Descent
- Automatic Traction Control (ATC)
- SCR Automatic Battery Charger
- All Motion Alarm

*Provides indicator lights at platform control console for system distress, low fuel, 5 degree tilt light, and foot switch status.

Individual Options:

- 30 x 48 in. (0.76 x 1.22 m) Platform
- Mesh to Top Rail Bolt-on Aluminum Soft Touch System (E/M600J only)
- Platform Padding (30 x 72 in. Platform)
- 1/2 in. Airline to Platform
- Foam-Filled Tires
- 1200W Inverter
- Hostile Environment Kit¹
- UL® EE Rating²
- Tow Package³
- Light Package⁴
- Platform Worklights
- Flashing Amber Beacon

1. Includes console cover, boom wipers and cylinder bellows.
2. Not available on Multi-Powered models.
3. 2WD only.
4. Includes head and taillights, and platform worklights.

Note: Some options may increase lead time, and some option combinations may not be available.

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs our products with our exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) full years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453 and ANSI A92.5-1992 as originally manufactured for intended applications.

JLG Industries, Inc.

1 JLG Drive, McConnellsburg, PA 17233-9533
Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

